



ROMCABLU

ROMCABLU srl.

vanzari@romcablu.com , rom.cablu@hotmail.com
impex@romcablu.com , romcablu@hotmail.com



0728 062886

We produce cable since 1994

Producem cablu din 1994

CMP1Y

Romcablu

Romcablu

2x7(4x0.40 Cu+3x0.50 CSS)

Cablul bifilar torsadat , izolat in PVC **Highly flexible PVC-insulated cables**

Standardul de produs I Standard of Product

Romcablu 2012/01/01

Domeniul de utilizare Cablul bifilar torsadat, izolat in PVC pentru impuscare, Utilizat in industria miniera

Tensiune de incercare:2300 V ca ,50 Hz

Rezistenta electrica max la 20 ° C:2x48 Ω/km

Rezistenta de izolatie , la 70°C: min 1 MΩxm .

Temperatura de lucru : -20÷ +40°C

Conductor este format din 4 sarme de cupru de 0.4 mm si 3 sarme de otel-cuprat de 0.5mm

Izolatia PVC tip YI1

Cod de culori : alb / verde sau alb /albastru

Applications: PVC-insulated twisted pair firing cable for the mining industry

Test voltage: 2300 V AC, 50 Hz

Max. electrical resistance at 20 ° C: 2x48 Ω/km

Insulation resistance at 70°C: min. 1 MΩxm .

Operational temperature: -20÷ +40°C

Conductor The conductor is made up of 4 x 0.4 mm copper wires and 3 x 0.5 mm copper-coated steel wires.

Insulation PVC type YI1

Color cod : White / green or white / blue

Conductori Cores (nxmm) J-YY	Grosime izolatie Insulation thickness (mm)	Grosime manta Sheath thickness (mm)	exterior Outer Ø (mm)	Max.cond. resistance (ohm/km)	Greutate Weight kg/km
CMP1Y 2x7x0.4	0.8	0.62	85-122	2X48	32-35