



ROMCABLU

# ROMCABLU Srl.

vanzari@romcablu.com - rom.cablu@hotmail.com  
www.romcablu.com www.rom-cablu.ro



## Cordoane flexibile cu izolatie si manta din PVC Flexible cords PVCinsulated MYYU, MYYUP H03VV-F, H03VVH2-F



### Constructie

Conductor flexibil din cupru, clasa5  
Izolatie dinPVC  
Manta dinPVC

### Specificatia tehnica

Tensiunea nom.: 300/300 V  
Temperatura minima:  
– instalare si manipulare: +5 °C  
– depozitare: –40 °C  
Temperatura max. de depozitare: +40°C  
Temperatura de lucru: min. –25°C max. +70°C  
Utilizare: conectarea aparaturii casnice si de birou, supuse la solicitari usoare, in medii umede  
Culoarea mantalei: alb, negru  
Standard de fabricatie: HD 21.5.S3  
Identificare conductori conf. VDE 0293, HD 308  
Ambalare: colaci de 100, cutii carton, bobine.

### Construction

Stranded copper conductor, class5  
PVCinsulation  
PVCsheath

### Technical specification

Rated voltage: 300/300 V  
Min. perm. temp.  
– with installation and handling: +5 °C  
– storage: –40°C  
Max. perm. storage temp.: +40°C  
Operating temperature: min. –25°C max. +70°C  
Use: Connections of household and office electrical appliances working with light mechanical stress, connections of appliances working in humid and wet rooms .  
Colour of sheath: white, black  
Manufactured according to: HD 21.5.S3  
Core identification acc. to VDE 0293, HD 308  
Packing: coils 100 m, boxes, reels

Conductori Cores (nxmm <sup>2</sup> ) MYYUP	Forma (Shape) conductor	Gr.izolatie Insulation thick.(mm)	Gr. manta (mm) sheath thick.(mm)	exterior Ø Outer (mm)	Cupru Copper kg/km	Cablu Cable kg/km
2X0.5	rm	0.5	0.6	5,1X3,1	8	29
2X0.75	rm	0.5	0.6	5,5X3,4	12	35
2X1	rm	0.5	0.6	5,8X3,5	17	41
2X1.5	rm	0.5	0.6	6,4X3,8	25	52

ru – conductor rotund unifilar | round solid conductor  
rm – conductor rotund multifilar | round stranded conductor  
sm –conductor sector multifilar | stranded sector shaped conductor